

Litepanels Gemini 2x1 Soft GEMINI_002



General Specifications

DXOMARK Image Labs Reference	GEMINI_002
Dimensions (including yoke)	748 x 529 x 176 mm
Material	Aluminum (housing)
Color	Black
Weight (including yoke)	10.1 Kg
Remote control	DMX (XLR 5-Pin and RJ45)
Fixture Mounting	1-1/8" (28mm) Stud
HS Code	9405.42.3990
Country of origin	China

Electrical specifications

AC Input Power	100 - 240 VAC, 50 / 60 Hz
DC Input Power	13 ~ 28 VDC
Power Consumption	350 W

Photometric specifications	
Spectrum type	LED (RGBWW)
Color Temperature setting	2700 - 10 000 K
Color Rendering Index at 100% *	> 95 from 2700 to 6500 K > 90 from 7500 to 10000 K
Dimming	0 to 100% (0.1% steps)
Luminance**	65 - 65 000 Cd/m ²
Lit surface area	580 x 260 mm
Flicker free	YES
Warming delay***	12 min

* CRI depends on the color temperature and intensity settings. Lower intensity decreases the CRI.

** Max and min luminance may vary slightly on each device and selected color temperature.

*** Time required for intensity variations to be less than 1%

Accessories included

1 Europe to USA power plug adapter

Description

The Gemini 2x1 Led panel is an RGB flicker free Led Fixture allowing powerful backlight illumination of DXOMARK transmissive 700 x 310 mm charts.